



mobiMASTER-980 I-ZVABD

12 V-54 l/min-EBZD-F

Item number: 26 542
EAN: 4048358265425
Discount group: D

Technical data

Tank volume (l): 980
 Material tank: LLDPE (linear low density polyethylene)
 Temperature range (°C): -10 / +40
 UN approval: un 31H2/Z/** **/CZ/IMET 2385/0/1284kg

Pump
 Brand: FMT Swiss AG
 Connecting cable with battery terminal clips, length (m): 3
Hydraulic data
 Pump design: vane pump, selfpriming
 Delivery rate under free discharge (l/min): 54
 Discharge pressure up to (bar): 1,8
 Pumping media: Fuel oil, diesel, HVO 100
Motor data
 Voltage (V): 12 V DC
 Power consumption (A): 30
 Fuse (A): 40 A plug-in fuse
 Duty cycle (min) under free discharge max.: 180
 Run time (min) when dispensing valve is closed max.: 2
 Safety class: IP66

Digital in-line meter
 Display: 5 digits display

Dimensions LxWxH (mm): 1400 x 1050 x 1143

Specification

- Single-walled tank (45 324)
- Universal fixation loops for integral shackles (89 823)
- Ventilation valve (45 140)
- Level indicator (92 778)
- Tank cap with seal (45 151)
- Gas spring kit (45 153)
- Safety valve between tank and pump (19 779)
- Suction hose, 0,65 m, DN 19, G 1" male, G 1" female (92 782)
- Non-return valve with filter (91 146 001)
- Vane pump, with integral bypass (23 406 966)
- On/off switch (81 293)
- In-line meter, digital (23 190)
- Automatic nozzle valve with German design approval and swivel, ZVABD (23 168)
- Discharge hose, 6 m, DN 19, G 1" male, G 1" female (23 155 958)
- Diesel-exchange filter, 10 µm (23 290)

Special notes

- Movable under load
- Diffusion resistant
- UV-resistant (UV index 12)
- Can be moved while filled with a forklift or crane
- Pump area closed with a cover to protect against weather conditions
- Manufacturer's warranty on the tank, valid for 5 years from the date of delivery, and 2 years warranty on built-in and attachment parts
- Storage of petrol in the tank is strictly forbidden.
- A leakage test is recommended to be effected every 2 1/2 years, a general test every 5 years
- UN/ADR approval for ares® mobiMASTER tanks and FMT® diesel pump systems
- UN-approval
- Production under permanent control of the German TÜV

Packaging

Dimensions LxWxH (mm):	1400 x 1050 x 1143
Packing unit:	1,0