

TANK FUEL APPROVED

containment basin 110%



Tutte le immagini sono meramente a scopo illustrativo. L'azienda si riserva di apportare qualsiasi tipo di modifica senza alcuna comunicazione e/o autorizzazione preliminare.

Diesel Tanks, TANK FUEL CUBE 56 1X, homologated by the Ministry of Internal Affairs according to Italian law (n. 3704/1366/80/37/44), D.M. 19/03/90 and D.M. 22 November 2017.

Steel tanks for Diesel fuel storage and delivery, homologated by Italian Ministry of Interior. Horizontal cylindrical mono-skin tanks manufactured by using shell plates and dished ends made of carbon steel quality S235JR according to UNI EN 10025, watertight electro-welded (submerged arc welding process), provided with anti-roll supports, primed with a rust preventing layer and externally treated with two coats of primer and a final finish of two coatings of synthetic metallic GREY paint. Tanks are delivered pressure-tested and ready-to use.

Equipment: collection basin able to hold 110% of total quantity of the tank, bottom discharge with cap, 1" suction hose with no-return valve and calibrated spring, suction filter, 1" ball valve, manhole 400mm diameter with a 3-inch opening with a lockable brass bayonet fastening and a 90% load limiting valve, 1" 1/2 vent with brass fire-barrier terminal, mechanical floating level indicator, minimum level pump locking device, electric panel, plug for the connection of the earth cable, service ladder (with non-slip steps, handrail for TF 5.000-7000-9000 or grab handle for TF 1200-2000-3000). A protection roof is available (as option) made of a tubular metal galvanised profile and cover. A water separator filter is also available for all versions (as option)

OPTIONAL



Mechanical dispensing system:

CUBE 56
 Dispensing unit (nominal flow rate 56 l/min) with single-phase, self-priming volumetric electric pump with built-in filter, with oscillating disc volumetric counter mod.K33, aluminium body, automatic dispensing nozzle mod. HUSCKY and 4-metre hose with 1" fittings; all enclosed in a self-supporting pressed sheet metal structure with anti-corrosion treatment, nozzle holder in the structure and equipped with an external start and stop lever (electric panel and minimum level probe are optional).

PRICE LIST

Code	Description	Capacity	Flow rate
PFTF-1.2CUBE561X	TANK-FUEL APPROVED lts. 1.200 with basin 110% mod. CUBE 56-without roof	1.200 lt.	56 lt/min
PFTF-2CUBE561X	TANK-FUEL APPROVED lts. 2.000 with basin 110% mod. CUBE 56-without roof	2.000 lt.	56 lt/min
PFTF-3CUBE56/A1X	TANK-FUEL APPROVED lts. 3.000 with basin 110% mod. CUBE 56-without roof	3.000 lt.	56 lt/min
PFTF-5CUBE56/A1X	TANK-FUEL APPROVED lts. 5.000 with basin 110% mod. CUBE 56-without roof	5.000 lt.	56 lt/min
PFTF-7CUBE56/A1X	TANK-FUEL APPROVED lts. 7.000 with basin 110% mod. CUBE 56-without roof	7.000 lt.	56 lt/min
PFTF-9CUBE561X	TANK-FUEL APPROVED lts. 9.000 with basin 110% mod. CUBE 56-without roof	9.000 lt.	56 lt/min

DIMENSIONS/WEIGHT

Code	Capacity	Diameter	Length	Basin dimension	Roof dimension	Weight Kg
PFTF-1.2CUBE561X	1.200 liters	950 mm	2.000 mm	1200x2100xh530mm	1600x2200mm	375 Kg
PFTF-2CUBE561X	2.000 liters	1.270 mm	1.500 mm	1400x2200xh720mm	1600x2200mm	480 Kg
PFTF-3CUBE56/A1X	3.000 liters	1.500 mm	1.840 mm	1650x2400xh870mm	1800x2500mm	610 Kg
PFTF-5CUBE56/A1X	5.000 liters	1.800 mm	2.150 mm	2250x2430xh1050mm	2350x2500mm	815 Kg
PFTF-7CUBE56/A1X	7.000 liters	1.800 mm	2.900 mm	2250x3260xh1050mm	2350x3500mm	991 Kg
PFTF-9CUBE561X	9.000 liters	1.800 mm	3.660 mm	2160x4100xh1120mm	2350x4400mm	1140 Kg

Code	Description
PFTT-12001X	ROOF FOR TF 1200 1X
PFTT-20001X	ROOF FOR TF 2000 1X
PFTT-3000/A1X	ROOF FOR TF 3000/A 1X
PFTT-5000/A1X	ROOF FOR TF 5000/A 1X
PFTT-7000/A1X	ROOF FOR TF 7000/A 1X
PFTT-90001X	ROOF FOR TF 9000/A 1X

ACCESSORIES ON DEMAND

Code	Description
ACTF/FILSEP60	WATER SEPARATOR FILTER (60lt/min)
ACGR-P/TB55/R	SURCHARGE FOR ADDITIONAL HOSE
ACTF-FILWC*	CLEAR CAPTOR FILTER WC WATER SEP. 30 mn
ACTF-FILCC*	CLEAR CAPTOR FILTER CC IMPURITY 5 mn
ACTF-QELCUB	ELECTRIC PANEL FOR TANK-FUEL
ACTF-SNDLIV	LEVEL PROBE IEG S1M TANK FUEL

* FILTERS WITH TRANSPARENT SHELL, BLEED VALVE AND ADDITIONAL CARTRIDGE(SPARE)

cube56